



## PURITY™ FG WO WHITE MINERAL OILS

### Introduction

Petro-Canada's PURITY™ FG WO oils are ultra pure, food grade white mineral oils specially formulated for food processing and other industrial use where contact of the lubricant with food is only incidental.

Using the HT purity process, Petro-Canada produces 99.9% pure, crystal clear white mineral oils – among the purest in the world. Blended with up to 10 ppm of Vitamin E as a stabilizer, PURITY FG WO oils are ideally suited for applications that require a straight, non-toxic white mineral oil.

PURITY FG WO oils meet standards that are among the highest for food industry purity and fit perfectly in HACCP (Hazard Analysis and Critical Control Point) and GMP (Good Manufacturing Practice) plans. They are H1 and 3H registered by NSF and are acceptable for use in food processing facilities in Canada (10 and 40 grades pending).

### Features and Benefits

- **Low volatility**
  - Helps minimize consumption
- **Includes an oxidation inhibitor for stability**
  - Extended shelf life
- **Odourless and tasteless**
- **Excellent pour characteristic**
  - Good fluidity at low temperatures
- **Water white colour, helps minimize the risk of staining**
- **Fully approved for use in and around food processing areas**
  - H1 registered by NSF as a lubricant with incidental food contact for use in and around food processing areas
  - 3H registered by NSF for use as a release agent on hard surfaces to prevent food from adhering during processing

- Acceptable for use in food processing facilities in Canada.
- Certified Kosher and Pareve by Star K
- Certified Halal by IFANCA
- All fluid components comply with United States Food and Drug Administration (FDA) regulations:
  - CFR 21, Section 172.878 - White Mineral Oil
  - CFR 21, Section 178.3620 (a) - White Mineral Oil
  - CFR 21, Section 178.3570 - Lubricants with Incidental Food Contact
  - CFR 21, Section 176.170 - Components of paper and paperboard in contact with aqueous and fatty foods
- **PURITY FG WO 35, 40, 68 and 90 meet mineral oils, USP (United States Pharmacopoeia standards)**
- **PURITY FG WO 10 and 15 meet Light Mineral Oil, NF (National Formulary Standards)**
- **PURITY FG WO 15 is approved by the United States Department of Agriculture (USDA) for use as a protecting oil on Shell Eggs processed in plants operating under the USDA voluntary shell egg grading program**
- **PURITY FG WO 90 is certified for NSF/ANSI Standard 60 for use in drinking water treatment applications (eg. well pump lubricant)**

#### What is the HT difference?

Petro-Canada starts with the HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.



Nonfood Compounds  
Program Listed H1

## Applications

PURITY FG WO oils may be safely used where an approved food grade or inert white mineral oil is required. General applications include incidental food contact in producing, manufacturing, processing, treating or packaging food.

Specific applications include:

- Rust and corrosion prevention for knives and cutting tables used in food preparation
- Release agents for molds and bakery pans
- Plasticizers

- Moisture resistant coatings on food packaging
- Dust suppressants
- Cleaning agent for stainless steel
- Shell egg protecting oil to retain freshness (15 grade only)

Prior to application (spraying) of the products in food handling areas, all food products should either be removed from the vicinity or otherwise protected from the spray.

## Typical Performance Data

PROPERTY	TEST METHOD	PURITY™ FG WO					
		WO 10	WO 15	WO 35	WO 40	WO 68	WO 90
Density, kg/L @ 15 °C	D4052	0.846	0.859	0.864	0.865	0.866	0.870
Gravity, °API @ 60 °F		35.7	33.2	32.2	32.0	31.9	31.1
Viscosity, cSt @ 40 °C / SUS @ 100 °F cSt @ 100 °C / SUS @ 210 °F	D445 / D2161	12.7 / 72	15 / 82	36.1 / 186	40.2 / 207	68 / 351	103 / 535
	D445 / D2161	3.1 / 36.6	3.4 / 37.8	5.8 / 45.4	6.2 / 46.6	8.9 / 55.7	11.8 / 66.5
Viscosity Index	D2270	100	98	105	100	100	104
Flash Point, COC, °C / °F	D92	190 / 374	175 / 347	220 / 428	240 / 464	255 / 491	266 / 511
Pour Point, °C / °F	D5950	-24 / -11	-18 / 0	-18 / 0	-18 / 0	-18 / 0	-15 / 5
Colour, Saybolt	D156	30	30	30	30	30	30

The values quoted above are typical of normal production. They do not constitute a specification.

## Health and Safety

To obtain Material Safety Data Sheets (MSDS), contact your Petro-Canada Lubricants representative, or one of Petro-Canada's TechData Info Lines.



## TechData Info Lines

To place an order, please call a Customer Order Management Representative at :

**Canada (English)** . . . . . Phone 1-800-268-5850  
**(French)** . . . . . Phone 1-800-576-1686  
**United States** . . . . . Phone 1-877-730-2369  
**Latin America** . . . . . Phone +1-416-730-2369  
**Europe** . . . . . Phone +1-416-730-2389  
**Asia** . . . . . Phone +1-416-730-2372  
**China** . . . . . Phone +86 (21) 6362-0066

To learn more about how Petro-Canada lubricants, specialty fluids, oils and greases can help maximize your equipment performance, savings and productivity, please contact us at :

**North America** . . . . . Phone 1-866-335-3369  
**Europe** . . . . . Phone +44 (0) 121-781-7264  
**Germany** . . . . . Phone +49 (0) 201-726-2913  
**Latin America** . . . . . Phone +1-416-730-2369  
**Asia** . . . . . Phone +1-416-730-2372  
**China** . . . . . Phone +86 (21) 6362-0066  
**E-mail** . . . . . sales@suncor.com

You can also e-mail us at [lubecsr@suncor.com](mailto:lubecsr@suncor.com)

Visit us on the web at [lubricants.petro-canada.ca](http://lubricants.petro-canada.ca)