SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	:	TRAXON ™ XL SYNTHETIC BLEND 80W-140
Product code	:	TRXL814IBC, TRXL814DRM, TRXL814DCT, TRXL814, TRXL814BLK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	These products are multipurpose automotive hypoid gear lubricants, suitable for use in lower temperatures in passenger cars, trucks and off-highway vehicles.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited
Wellington House, Starley Way
Birmingham International Park Solihull B37 7HB
United Kingdom

E-mail address of person responsible for the SDS	:	EUSDS@suncor.com

1.4 Emergency telephone number

Emergency telephone number	:	Suncor Energy: +1 403-296-3000; Poison Control Centre: Consult local telephone directory for emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Classification (67/548/EEC, 1999/45/EC)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

Additional Labelling:

EUH210 Safety data sheet available on request.
EUH208 May produce an allergic reaction.
Contains: Polysulfides, di-tert-Bu and Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0 276-737-9 01-2119474878-16-0001		Asp. Tox. 1;	20 - 30
Mineral oil			Asp. Tox. 1; H304	1 - 10
Polysulfides, di-tert-Bu	68937-96-2 273-103-3	Xi; R38-R43-R52/53	Aquatic Chronic 3; H412 Skin Sens. 1; H317	2.5 - 10
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	931-384-6	Xn-N; R22-R41-R43-R51/53	Acute Tox. 4; H302 Aquatic Chronic 2; H411 Eye Dam. 1; H318 Skin Sens. 1; H317	1 - 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.

In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.

If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), smoke and irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Advice on protection against fire and explosion : None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any

Petro-Canada is a Suncor Energy business. ™ Trademark of Suncor Energy Inc. Used under licence.

exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection	:	Wear face-shield and protective suit for abnormal processing problems.
Hand protection		
Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Protective measures	:	Wash contaminated clothing before re-use. No special protective equipment required.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	viscous liquid
Colour	:	Colourless to pale yellow.
Odour	:	Mild petroleum oil like.
Odour Threshold	:	No data available
pH	:	No data available
Pour point	:	-36 °C (-33 °F)
Boiling point/boiling range	:	No data available
Flash point	:	193 °C (379 °F) Method: Cleveland open cup
Fire Point	:	No data available
Auto-Ignition Temperature	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.878 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	254.8 cSt (40 °C / 104 °F)
		25.24 cSt (100 °C / 212 °F)
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

9.2 Other information

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : May release COx, H2S, methacrylate monomers, aldehydes, alkyl mercaptans, sulfides, smoke and irritating vapours when heated to decomposition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:
Acute oral toxicity : LD50 Rat: > 5,000 mg/kg,

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

Acute inhalation toxicity	:	LC50 Rat: > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Rabbit: > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:
Result: No skin irritation

Serious eye damage/eye irritation

Product:

Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:
Result: No eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae	:	Remarks: No data available
Toxicity to bacteria	:	Remarks: No data available

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of as hazardous waste in compliance with local and national regulations. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

SECTION 14: Transport information

International Regulation

IATA-DGR
Not regulated as a dangerous good

IMDG-Code
Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

49 CFR
Not regulated as a dangerous good
TDG
Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class (Germany)	:	WGK 2	water endangering

The components of this product are reported in the following inventories:

DSL	:	On the inventory, or in compliance with the inventory
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
IECSC	:	On the inventory, or in compliance with the inventory
EINECS	:	On the inventory, or in compliance with the inventory

15.2 Chemical Safety Assessment

SECTION 16: Other information

Full text of R-Phrases

R22	:	Harmful if swallowed.
R38	:	Irritating to skin.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.

R41	:	Risk of serious damage to eyes.
R43	:	May cause sensitisation by skin contact.
R51/53	:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of H-Statements

H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Chronic aquatic toxicity
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Skin Sens.	:	Skin sensitisation

For Copy of (M)SDS	:	Internet: lubricants.petro-canada.ca/msds Europe, telephone: 00-800-7387-6000 For Product Safety Information: 1 905-804-4752

Prepared by	:	Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Petro-Canada is a Suncor Energy business.
™ Trademark of Suncor Energy Inc. Used under licence.