

XL-0715/900

CLEANING GREASE FOR BEARINGS USING XL-0715/002

XL-0715/900 Is a solvent containing grease designed to loosen and rejuvenate bearings that have residual or dried **XL-0715/002**.

XL-0715/900 has been formulated with the same synthetic PAO base oil as the XL0715 to provide superior lubrication as it cleans bearings.

N.B. Due to the thixotropic and cleansing properties of the **XL-0715/900** certain precautions must be taken not to over lubricate bearings Apply **XL-0715/900** with the same equipment used for **XL-0715/002**. Inspect bearings after lubricating and observe old grease as it is forced out and determine the 'cleaning' cycle. Use only enough **XL-0715/900** to clean bearing then return application to **XL-0715/002**

| TYPICAL SPECIFICATIONS | |
|---|-------------------|
| Product Code: XL-0715 | /900 |
| N.L.G.I. Grade: | 1 - 1.5 |
| Dropping Point (°C) (ASTM D-2265) | None |
| Melting Point (°C) | None |
| Copper Strip Test (163°C for 3 hours) | Negative |
| Texture | Soft / Adhesive |
| Colour | Yellow |
| Timken OK Load (kg) (ASTM D-2509) | 22 |
| Type of thickener | Silica |
| Oil Separation (24hrs @ 25°C) (ASTM D-1742) | N/A |
| Temperature Range (°C) | -17 to 399 |
| Minimum Dispensing Temperature (°C) | -1 |
| Solvent Type | Trichloroethylene |