255 Avenue Labrosee
Pointe-Claire, Quebec
H9R 1A3, Canada
1-800-567-5823
www.thermal-lube.com

XL-7315

SYNTHETIC AUTOMOTIVE GEAR OIL GL-5

XL-7315 series are 100% synthetic, fully formulated automotive (GL-5) gear lubes that offer optimum performance in the broadest range of ambient temperatures and environmental conditions.

XL-7315 series provides:

- Energy conservation due to reduced friction
- Component wear reduction
- Reduced oil consumption
- Compatibility with mineral oils
- Increased maintenance intervals
- High and low temperature viscosity stability

TYPICAL SPECIFICATIONS						
Product Code: XL-7315	**/759**	**/801**	**/890**	**/090**	**/140**	**/220**
SAE Grade	75W90	80W140	80W90	90	140	--
ISO Grade	--	--	--	--		220
AGMA Grade	4 EP	5-6 EP	4 EP	5 EP	6 EP	5 EP
Viscosity (cSt @ 40°C) (ASTM D-445)	115	240	135	107	263	225
Viscosity (cSt @ 100°C) (ASTM D-445)	18.5	31.0	18.0	14.2	26.4	25.9
Viscosity Index	180	171	149	135	132	147
Flash Point (°C)	207	220	208	210	235	235
Pour Point (°C) (ASTM D-97)	-50	-40	-47	-36	-30	-32
Colour	Green	Green	Green	Green	Green	Green