255 Avenue Labrosee
Pointe-Claire, Quebec
H9R 1A3, Canada
1-800-567-5823
www.thermal-lube.com

XL-7381

Superior synthetic tractor lube

XL-7381is a state-of-the-art lubricant designed for the most rigorous applications and equipment. **XL-7381** is recommended for use in farm, construction, and forestry equipment, using a single type of oil to all these parts:

- Gears
- Pumps
- Differentials
- Bearings
- Disc brakes
- Transmissions
- Clutch (PTO)
- Axles

XL-7381 rises above the competition:

- Contains special additives for maximum load with minimum wear to gears and drive trains
- Reduces butting and vibration in disc brakes, leading to superior brake performance
- Prevents clutches from slipping and burning, which allows for faster braking
- Easily filtered and highly water-resistant
- Contains additives to prevent rust and corrosion, even in the presence of water
- Extends the life of gaskets and seals

XL-7381 will work well at all temperatures – hydraulic equipment will start up faster, and the need for seasonal oil changes will be eliminated

TYPICAL SPECIFICATIONS	
Product Code: XL-7381	**/080**
SAE Grade	80W
Viscosity (cSt @ 40°C) (ASTM D-445)	56
Viscosity (cSt @ 100°C) (ASTM D-445)	9.1
Viscosity (cP @ -40°C) (ASTM D-2983)	55,000
Flash Point (°C)	>215
Pour Point (°C) (ASTM D-97)	-42
Specific Gravity (g/ml)	0.88