

## **XL-7381**

### **Superior synthetic tractor lube**

**XL-7381** is a state-of-the-art lubricant designed for the most rigorous applications and equipment. **XL-7381** is recommended for use in farm, construction, and forestry equipment, using a single type of oil to all these parts:

- Gears
- Pumps
- Differentials
- Bearings
- Disc brakes
- Transmissions
- Clutch (PTO)
- Axles

**XL-7381** rises above the competition:

- Contains special additives for maximum load with minimum wear to gears and drive trains
- Reduces butting and vibration in disc brakes, leading to superior brake performance
- Prevents clutches from slipping and burning, which allows for faster braking
- Easily filtered and highly water-resistant
- Contains additives to prevent rust and corrosion, even in the presence of water
- Extends the life of gaskets and seals

**XL-7381** will work well at all temperatures - hydraulic equipment will start up faster, and the need for seasonal oil changes will be eliminated

<b>TYPICAL SPECIFICATIONS</b>	
<b>Product Code: XL-7381</b>	<b>/080</b>
SAE Grade	80W
Viscosity (cSt @ 40°C) (ASTM D-445)	56
Viscosity (cSt @ 100°C) (ASTM D-445)	9.1
Viscosity (cP @ -40°C) (ASTM D-2983)	55,000
Flash Point (°C)	>215
Pour Point (°C) (ASTM D-97)	-42
Specific Gravity (g/ml)	0.88