255 Avenue Labrosee
Pointe-Claire, Quebec
H9R 1A3, Canada
1-800-567-5823
www.thermal-lube.com

XL-8375

SEMI-SYNTHETIC FUEL ADDITIVE
HIGH PERFORMANCE TWO-CYCLE ENGINES

XL-8375 is an all-weather semi-synthetic oil designed for use year-round in applications and equipment including **snowmobiles, outboards, chainsaws, lawnmowers, motorcycles, etc.**

XL-8375 meets requirements of both the Boating Institute of America (BIA) and the National Marine Manufacturers Association (NMMA) specification TC-W3.

- Recommended for both water- and air- cooled engines.
- Formulated to blend with any gasoline or alcohol pre-mix or injector system.
- Designed to reduce friction and aid fuel economy.
- Extends engine life.
- Burns cleaner to reduce exhaust pollution.
- Eliminates carbon build-up to prevent spark plug fouling.
- Provides superior rust and oxidation protection with excellent seal compatibility.
- Low temperature service. Pour point of -35°C.
- Can be blended up to 100:1 ratio.
- Does not gel.
- Will not block filter.

Follow equipment manufacturer's recommendations for mixing proportions.

FUEL:OIL MIXING RATIOS										
Mix Ratios (follow equipment manufacturers' blend ratios)	7:1	10:1	16:1	20:1	24:1	32:1	40:1	50:1	75:1	100:1
ml Oil per 5 litres of Fuel	715	500	315	250	210	155	125	100	65	50
Fl. Oz. Oil per USG of fuel	18.3	12.8	7.9	6.4	5.3	4.0	3.2	2.6	1.7	1.2

TYPICAL SPECIFICATIONS	
Product Code: XL-8375	
SAE Grade	40 / 30
Viscosity Index	120
Flash Point (°C)	163
Fire Point (°C)	193
Pour Point (°C) (ASTM D-97)	-46
Colour	Dark Green