

## XL-0835

# POLYON® SYNTHETIC GL-5 TACKY GEAR OIL

**XL-0835** Synthetic Gear Lube with Teflon® is a new high-tech product formulated to out-perform conventional petroleum gear lubes. XL-0835 demonstrates excellent ability to cool and reduce friction in all weather, giving you longer engine life and better fuel economy.

**XL-0835** offers:

- Low oil consumption
- Compatible with mineral oils
- Longer periods between maintenance
- Viscosity stability at high and low temperatures
- Reduced friction, heat and wear
- High Load Capacity: will not break down when exposed to heat shearing forces
- Seal and Gasket Protection: reduce leakage, swelling, shrinkage and hardening
- Extreme Cold Weather Performance: quick start-up, instant lubrication, easier shifting and increased fuel economy
- Rust and Corrosion Protection: will protect gears and sprockets during down periods
- Not affected by water

**Approved by Agriculture Canada for use in federally inspected food plants  
 where there is no possibility of food contact**

<b>TYPICAL SPECIFICATIONS</b>								
<b>Product Code: XL-0835</b>	<b>/090</b>	<b>/140</b>	<b>/759</b>	<b>/801</b>	<b>/809</b>	<b>/220</b>	<b>/320</b>	<b>/460</b>
SAE Grade	90	140	75W90	80W140	80W90	-	-	-
ISO Grade	-	-	-	-	-	220	320	460
AGMA Grade	5-EP	6-EP	4-EP	5-6 EP	4-EP	5-EP	6-EP	7-EP
API Class	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5
Viscosity (cst @ 40°C) (ASTM D-445)	107	263	130	240	135	225	310	475
Viscosity (cst @ 100°C) (ASTM D-445)	14.2	26.4	17.5	31.0	18.0	25.9	32.4	42.0
Viscosity Index	0135	132	148	171	149	147	145	138
Flash Point (°C)	210	235	207	220	208	265	238	238
Pour Point (°C)	-36	-30	<-50	-40	-47	-32	-28	-22
Colour				Natural				

POLYON® is a Registered Trademark of Thermal-Lube Inc.  
 Teflon® is a Registered Trademark of DuPont