

## **XL-7328**

### **SYNTHETIC AIR LINE OIL**

**XL-7328** is an extreme pressure synthetic lubricant designed for pneumatic equipment.

**XL-7328** exhibits excellent anti-rust and corrosion properties and can be used in reciprocating, rotary, or impact equipment under the most severe ambient operating conditions and climates.

**XL-7328** is formulated with emulsifiers and tackifiers, ensuring a high degree of resistance to wash-off, and strong adhesion to reciprocating parts.

**XL-7328** is approved by the Canadian Food Inspection Agency (CFIA) for use in food processing plants.

**XL-7328** is available in several standard viscosity grades to meet most air-line tool requirements.

<b>XL-7328/022</b>	ISO #22	light	(winter grade)
<b>XL-7328/032</b>	ISO #32	medium	(winter grade)
<b>XL-7328/046</b>	ISO #46	thick	(winter grade)
<b>XL-7328/150</b>	ISO #150	medium	(standard grade)
<b>XL-7328/220</b>	ISO #220	thick	(standard grade)

<b>TYPICAL SPECIFICATIONS</b>							
<b>Product Code: XL-7328</b>	<b>/015</b>	<b>/022</b>	<b>/032</b>	<b>/046</b>	<b>/100</b>	<b>/150</b>	<b>/220</b>
SAE Grade	-	-	5W	10W	30	40	50
ISO Grade	15	22	32	46	100	150	220
Viscosity (cSt @ 40°C) (ASTM D-445)	14.8	23.7	31.8	44.2	95.4	147	221
Viscosity (cSt @ 100°C) (ASTM D-445)	3.6	4.8	5.8	7.3	13.5	17.3	22.0
Viscosity Index	129	126	126	128	142	128	121
Flash Point (°C)	180	182	185	188	208	215	241
Pour Point (°C) (ASTM D-97)	-55	-53	-52	-46	-38	-36	-35
Specific Gravity (g/ml)	0.83	0.86	0.86	0.87	0.88	0.89	0.90