

XL-7390

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

XL-7390 is formulated from synthetic base stocks to provide longer parts life and smooth, positive gear shifting.

XL-7390 exhibits excellent high and low temperature stability and maintains a high degree of shear stability under severe operating conditions.

XL-7390 meets or exceeds the following specifications:

- Dextron III®, Dextron II®, Dextron®
- Mercon II®, Mercon®
- Type A Suffix A, Type A
- Ford M2C-138C, M2C-166H,
- Allison C-4
- Caterpillar TO-2 , TO-4

Also: Sperry-Vickers, Denison, & Sundstrand pump systems

TYPICAL SPECIFICATIONS	
Product Code: XL-7390	/030
Viscosity (cSt @ 40°C) (ASTM D-445)	35.5
Viscosity (cSt @ 100°C) (ASTM D-445)	7.5
Viscosity (cP @ -40°C) (ASTM D-2983)	16,000
Viscosity (cP @ -35°C) (ASTM D-2983)	7,600
Viscosity (cP @ -30°C) (ASTM D-2983)	3,200
Viscosity (cP @ -20°C) (ASTM D-2983)	950
Viscosity Index	186
Flash Point (°C)	225
Pour Point (°C) (ASTM D-97)	-55
Copper Strip Test (163°C for 3 hours)	Pass
Specific Gravity (g/ml)	0.86
Seal Swell	Pass
Foam Test	Pass+
	<small>DEXTRON® is a Registered Trademark of General Motors</small>
	<small>MERCON® is a Registered Trademark of Ford</small>

DEXTRON® is a Registered Trademark of General Motors
 MERCON® is a Registered Trademark of Ford

